


Tener una aplicación con AngularJS y se requiere tener multiples vistas con multiples htmls, aquí una POC. Para esto se utiliza ui-router (<https://github.com/angular-ui/ui-router>)



## Vista 1

tipo 1

## Vista 2

tipo 2

## Vista 3

tipo 3

The screenshot shows two files in an IDE. The left pane shows `index.html` with the following content:

```

1 <!doctype html>
2 <html ng-app="app">
3 <head>
4 <title>IBM</title>
5 <link rel="shortcut icon" href="favicon.ico">
6 <script type="text/javascript" src="js/angular-1.5.5.js"></script>
7 <script type="text/javascript" src="js/angular-ui-router.js"></script>
8 <script type="text/javascript" src="js/code.js"></script>
9 </head>
10 <body>
11 <div ui-view="box1" style="background: #ECCF53"></div>
12 <div ui-view="box2" style="background: #E5EDD5"></div>
13 <div ui-view="box3" style="background: #FCE6CE"></div>
14 </body>
15 </html>
    
```

The right pane shows `code.js` with the following content:

```

1 var app = angular.module("app", ['ui.router']);
2
3 app.config(['$stateProvider', '$urlRouterProvider',
4 function ($stateProvider, $urlRouterProvider) {
5   $urlRouterProvider.otherwise('/');
6   $stateProvider
7     .state('home', {
8     url: '/',
9     views: {
10      'box1': {
11        templateUrl: 'vista1.html',
12        controller: function($scope) {
13          $scope.mensaje1 = "tipo 1";
14        }
15      },
16      'box2': {
17        templateUrl: 'vista2.html',
18        controller: function($scope) {
19          $scope.mensaje2 = "tipo 2";
20        }
21      },
22      'box3': {
23        templateUrl: 'vista3.html',
24        controller: function($scope) {
25          $scope.mensaje3 = "tipo 3";
26        }
27      }
28    }
29  });
30 }
31 });
32
    
```

The screenshot shows three separate HTML files, each with a toolbar and a source view. The first file is `vista1.html`:

```

1 <h2>Vista 1</h2>
2 {{mensaje1}}
    
```

The second file is `vista2.html`:

```

1 <h2>Vista 2</h2>
2 {{mensaje2}}
    
```

The third file is `vista3.html`:

```

1 <h2>Vista 3</h2>
2 {{mensaje3}}
    
```

## Fuentes

- <https://www.sitepoint.com/write-modular-code-angular-ui-router-named-views/>
  - <https://github.com/angular-ui/ui-router/wiki/Multiple-Named-Views>
- 

## ArquitecturaIBM Consulting

