

grant_type: authorization_code

postman: /oauth2/authorize

35

The screenshot shows a Postman interface for a GET request to `/oauth2/authorize`. The request parameters are:

KEY	VALUE
scope	apiconnect
response_type	code
client_id	77ca9612085dcc7c776731fa6b275ec1

The response headers include:

KEY	VALUE
Authorization	Basic ar1wa1W8cGFyaQ==
Postman-Token	<calculated when request is sent>
Host	<calculated when request is sent>
User-Agent	PostmanRuntime/7.28.4
Accept	*/*
Accept-Encoding	gzip, deflate, br
Connection	keep-alive
X-IBM-Client-Id	77ca9612085dcc7c776731fa6b275ec1
X-IBM-Client-Secret	a70cb81a146c8a66f93aa2db37b4a98

The response body (raw) shows a redirect URL:

```

https://oam12.julopai.com/code=AALCCwYF19d3H1C3d1a5V2Zrsw4FFAg1u8-dq-u7Y...
    
```

grant_type: authorization_code

postman: /oauth2/token

36

The screenshot shows a POST request to `/oauth2/token` with the following parameters:

KEY	VALUE
client_id	77ca9612085dcc7c776731fa6b275ec1
client_secret	a70cb81a146c8a66f93aa2db37b4a98
grant_type	authorization_code
code	AAJL9WK57oAgmOToZ0-VbsrWYNYjZXCMB2UhiCCqe2Xk...

The response body (raw) shows the token response:

```

{
  "token_type": "Bearer",
  "access_token": "AAIglcd3YTk2HTiWdOVkY2H3Yzc3Hjcc%IzhnmYlzcV1YzE6pza2Cua18pIve6Kt90Pzocm3b3nCurpZc-h389Wpeua8Txs1-YF1B1Du7h6c3YbXum2_uYD6buZvff2NvGARsno3eTsaHDrTCm6FQ",
  "scope": "apiconnect",
  "expires_in": 3600,
  "consented_on": 1631972584
}
    
```



