









_1. Configuración de ODBC en Windows 7












_2. Configuración ODBC en IBM Integration Bus 10, ejecutar el comando mqsi y reiniciar el Integration Server



```
Administrador: IBM Integration Console 10.0.0.10 Developer Edition

Welcome to:

Enter an Integration Bus command e.g.
IIB toolkit, IIB help

C:\Program Files\IBM\IIB\10.0.0.10>mqsisetdbparms TESTNODE_IBM -n odbc::DS_SQLSERVER
-u sa -p root
BIP80711: Successful command completion.

C:\Program Files\IBM\IIB\10.0.0.10>_
```

Comando: `mqsisetdbparms <IS> -n odbc::<DATASOURCE> -u <USERNAME_BD> -p <PASSWORD_BD>`

Crear el servicio configurable

- `mqsisetdbparms TESTNODE_IBM -n odbc::DS_SQLSERVER -u sa -p root`

Validar el servicio configurable

- `mqsicvp TESTNODE_IBM -n DS_SQLSERVER`

Julio Pari (IT Architect IBM)



Si te ha interesado este artículo y deseas un apoyo o asesoría en algún requerimiento, envíame un mensaje a: (info@juliopari.com) o sino a través de LinkedIn:
<https://www.linkedin.com/in/juliopari/>
