

The screenshot shows the IBM Integration Bus configuration interface. On the left is a palette with various components like Web Services, SCA, WebSphere Adapters, Routing, .NET, Transformation, Construction, Input, Output, Throw, Trace, TryCatch, and FlowOrder. The main workspace displays a flow diagram with two nodes: 'IIB.JP.SENDTOSAP.REQ.01' and 'QR_SAP_01'. A 'Trace' node is connected to the output of 'QR_SAP_01' and is highlighted with a red box. Below the workspace, the 'Trace Node Properties - Trace' window is open, showing the following configuration:

| Trace Node Properties - Trace | |
|-------------------------------|---|
| Description | |
| Basic | Destination* File |
| Monitoring | File path C:\GECS\iiblogs\jpari\trama_xml_19.log |
| | Pattern \${CAST(ASBITSTREAM(Root.XMLNSC OPTIONS FolderBitStream CCSID 1208) AS CHAR CCSID 1208 ENCODING 0)} |
| | Message catalog |

Pattern: `${CAST(ASBITSTREAM(Root.XMLNSC OPTIONS FolderBitStream CCSID 1208) AS CHAR CCSID 1208 ENCODING 0)}`

Other case: `${CAST(ASBITSTREAM(Root OPTIONS FolderBitStream CCSID 1208) AS CHAR CCSID 1208 ENCODING 0)}`

ArquitecturaIBM Consulting

