

List:

- mqsiservice -v
- mqsilist
- mqsilist -r
- mqsilist *brkname*
- mqsilist *brkname* -d2
- mqsilist *brkname* -e *execgrp*
- mqsilist *brkname* -e *execgrp* -d 2
- ps -ef|grep Data
- dspmq
- dspmqver

Start/Stop:

- mqsistop *brkname* (-i -r)
- mqsistart *brkname*
- mqsistopmsgflow *broker* -e *execgrp*
- mqsistartmsgflow *broker* -e *execgrp*

Report:

- mqsireportproperties *brkname* -e *execgrp* -o AllReportableEntityNames -r
- mqsireportproperties *brkname* -e *execgrp* -o HTTPConnector -r
- mqsireportproperties *brkname* -e *execgrp* -o HTTPConnector -r
- mqsireportproperties *brkname* -e *execgrp* -o HTTPConnector -n port
- mqsireportproperties *brkname* -e *execgrp* -o ComIbmJVMMManager -r
- mqsireportproperties *brkname* -e *execgrp* -o ComIbmCacheManager -r
- mqsireportproperties *brkname* -b cachemanager -o CacheManager -r
- mqsireportproperties *brkname* -c JDBCProviders -o AllReportableEntityNames -r
- mqsireportproperties *brkname* -c JDBCProviders -o Oracle -r
- mqsireporttrace *brkName*
- mqsireportbroker *brkName*

Deploy:

- mqsiaapplybaroverride -b *origfile.bar* -p *props.properties* -o *updfile.bar*
- mqsideploy *brkname* -e *execgrp* -a *barfile.bar*

Delete:

- mqsideleteexecutiongroup *bkkname* -e *execgrp*

MQ runmqsc:

- runmqsc queuemgr (Type “end” to exit)
- display qlocal(myq*)

Run Listener:

- runmqslr -t tcp -p 10000 -m QMgrName &

Open IBM Integration/MQ Explorer and Integration Toolkit

- /opt/mqm/bin/MQExplorer OR /opt/mqm/bin/strmqcfg (*MQ Explorer*)
- /opt/IBM/IntegrationToolkit90/launcher (*IBM Integration Toolkit*)
- /opt/ibm/mqsi/9.0/sample/ConfigManagerProxy/StartConfigManagerProxyExercise

Enable/Disable Traces

- mqsichangetrace *brkName* -u -e *execGrp* -l debug -c 5000
- mqsireadlog *brkName* -u -e *execGrp* -o trace.xml (Location: /var/mqm/trace.xml)
- mqsiformatlog -i trace.xml -o formattrace.log

ArquitecturaIBM Consulting