



```
ibm-web-ext.xml
1 <?xml version="1.0" encoding="UTF-8"?>
2 <web-ext
3   xmlns="http://websphere.ibm.com/xml/ns/javaee"
4   xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
5   xsi:schemaLocation="http://websphere.ibm.com/xml/ns/javaee http://websphere.ibm.com/xml/ns/javaee/ibm-web-ext_1_1.xsd"
6   version="1.1">
7
8   <reload-interval value="3"/>
9   <enable-directory-browsing value="false"/>
10  <enable-file-serving value="true"/>
11  <enable-reloading value="true"/>
12  <enable-serving-servlets-by-class-name value="false" />
13  <context-root uri="/ejemplo01"/>
14 </web-ext>
15
```

Enterprise Applications

Enterprise Applications > Example01EAR > Context Root For Web Modules

Context Root For Web Modules

Configure values for context roots in web modules.

Web module	URI	Context Root
Example01	Example01.war,WEB-INF/web.xml	/ejemplo01

Cancel

Referencia: <http://www.freekb.net/Article?id=1647>

**Julio Pari (IT Architect IBM)**



Si te ha interesado este artículo y deseas un apoyo o asesoría en algún requerimiento, envíame un mensaje a: (info@juliopari.com) o sino a través de LinkedIn:  
<https://www.linkedin.com/in/juliopari/>

---