



The screenshot shows two files in an IDE. The first file, index.html, contains the following HTML code:

```
1 <!DOCTYPE html>
2 <html data-scriptportlet-combine-urls="true" class="no-js" lang="">
3   <head>
4   </head>
5   <body>
6     <h1>Script Application Example</h1>
7   </body>
8 </html>
```

The second file, sp-config.json, contains the following JSON code:

```
1 {
2   "contenthandlerPath": "\wps\mycontenthandler",
3   "mainHtmlFile": "index.html",
4   "portalUser": "wpsadmin",
5   "scriptPortletServer": "https://portaldemo.digitalexperience.ibm.com",
6   "wcmContentID": "03502e28-1f5b-4c40-8f45-104e83cfa85f",
7   "wcmContentTitle": "Script Application Example Demo 1"
8 }
```

Código:

```
<!DOCTYPE html>
<html data-scriptportlet-combine-urls="true" class="no-js" lang="">
  <head>
  </head>
  <body>
    <h1>Script Application Example</h1>
  </body>
</html>
```

```
{
"contenthandlerPath": "\wps\mycontenthandler",
"mainHtmlFile": "index.html",
"portalUser": "wpsadmin",
"scriptPortletServer": "https://portaldemo.digitalexperience.ibm.com",
"wcmContentID": "03502e28-1f5b-4c40-8f45-104e83cfa85f",
"wcmContentTitle": "Script Application Example Demo 1"
}
```

Julio Pari (IT Architect IBM)



Si te ha interesado este artículo y deseas un apoyo o asesoría en algún requerimiento, envíame un mensaje a: (info@juliopari.com) o sino a través de LinkedIn:
<https://www.linkedin.com/in/juliopari/>
