

```

1 =====
2 DYNAMIC
3 =====
4 <context-param>
5   <description>A regular expression that defines which of the resources in the WAR file can be served by the portal war datasource.</description>
6   <param-name>com.ibm.portal.resource.whitelist</param-name>
7   <param-value>.*</param-value>
8 </context-param>
9 <context-param>
10  <description>A regular expression that defines which of the resources in the WAR file cannot be served by the portal war datasource.</description>
11  <param-name>com.ibm.portal.resource.blacklist</param-name>
12  <param-value>WEB-INF/*</param-value>
13 </context-param>
14 =====
15 STATIC
16 =====
17 <context-param>
18   <description>A regular expression that defines which of the resources in the WAR file can be served by the portal war datasource.</description>
19   <param-name>com.ibm.portal.resource.whitelist</param-name>
20   <param-value>.*</param-value>
21 </context-param>
22 <context-param>
23   <description>A regular expression that defines which of the resources in the WAR file cannot be served by the portal war datasource.</description>
24   <param-name>com.ibm.portal.resource.blacklist</param-name>
25   <param-value>WEB-INF/*</param-value>
26 </context-param>
27 =====

```

=====

DYNAMIC

=====

<context-param>

<description>A regular expression that defines which of the resources in the WAR file can be served by the portal war datasource.</description>

<param-name>com.ibm.portal.resource.whitelist</param-name>

<param-value>.*</param-value>

</context-param>

<context-param>

<description>A regular expression that defines which of the resources in the WAR file cannot be served by the portal war datasource.</description>

<param-name>com.ibm.portal.resource.blacklist</param-name>

<param-value>WEB-INF/*</param-value>

</context-param>

=====

STATIC

=====

<context-param>

<description>A regular expression that defines which of the resources in the WAR file can be served by the portal war datasource.</description>

<param-name>com.ibm.portal.whitelist</param-name>

<param-value>.*</param-value>

</context-param>

<context-param>

<description>A regular expression that defines which of the resources in the WAR file cannot be served by the portal war datasource.</description>

<param-name>com.ibm.portal.blacklist</param-name>

```
<param-value>WEB-INF/*</param-value>  
</context-param>  
=====
```

Julio Pari (IT Architect IBM)



Si te ha interesado este artículo y deseas un apoyo o asesoría en algún requerimiento, envíame un mensaje a: (info@juliopari.com) o sino a través de LinkedIn:
<https://www.linkedin.com/in/juliopari/>
