

Para agregar una propiedad en el **DataSource** y poder setear el valor de **securityMechanism=13** se debe de ingresar a:

**Data sources > commDS > Custom properties**

Use this page to specify custom properties that your enterprise information system (EIS) requires for the resource providers and resource factories that you configure. For example, most database vendors require additional custom properties for data sources that access the database.

Preferences

New Delete

Select	Name	Value	Description	Required
<input type="checkbox"/>	<a href="#">securityMechanism</a>	13	Specifies the DRDA security mechanism. Possible values are: 3 (CLEAR TEXT PASSWORD SECURITY), 4 (USER ONLY SECURITY), 7 (ENCRYPTED PASSWORD SECURITY), 9 (ENCRYPTED USER AND PASSWORD SECURITY), or 11 (KERBEROS SECURITY). Please refer to DB2 manual for the constant value. If this property is specified, the specified security mechanism is the only mechanism that is used. If no value is specified for this property, 3 is used.	false

Page: 20 of 27 Total 27

Fuente: <http://www.torkwrench.com/2009/06/28/db2-and-configengine-security-mechanism-not-supported/>

## Julio Pari (IT Architect IBM)



Si te ha interesado este artículo y deseas un apoyo o asesoría en algún requerimiento, envíame un mensaje a: (info@juliopari.com) o sino a través de LinkedIn: <https://www.linkedin.com/in/juliopari/>